

# ASR1101M ASR1001M ASR1101M-D ASR1001M-D

## Vandal-proof RFID Reader



### Features

- Support RS485, Wiegand34 protocol(Wiegand 26 optional)
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- All-metal buttons with blue backlight
- Red and Green indicator LEDs
- Watch dog function ensure device free from halting
- Surface mounted installation



### Technical Specification

Mode	ASR1101M	ASR1001M	ASR1101M-D	ASR1001M-D
------	----------	----------	------------	------------

#### System

Main Processor	8 Bit
----------------	-------

#### Read

Read Format	13.56MHz	13.56MHz	125KHz	125KHz
Read Range	6-8cm (max.)			
Reading time	<0.1s			

#### Function

Tamper Alarm	Yes
Water-proof	IK08

#### Interface

To Controller	RS485, Wiegand34(Wiegand 26 optional)
---------------	---------------------------------------

#### General

Keyboard	12Key(0-9,*,#), number key 5 is a braille button
LED Indicator	Blue backlight
Beep Tone	Buzzer
Ingress protection	IK08, IP55
Power Supply	9-15VDC/100mA
Working Environment	-30°C~60°C
Working Humidity	≤95%
Dimension(W×D×H)	110mm*85mm*26mm
Weight	0.5Kg

### Dimensions

